
Providence City Plan Commission

April 19, 2022



AGENDA ITEM 2 ■ 94 SUMMER STREET



Proposed site plan



Aerial view of the site

Rendering of the proposed building

OVERVIEW

OWNER/ Crossroads Rhode Island, APPLICANT:

Owner and Applicant

PROJECT DESCRIPTION: The applicant is proposing to construct a

five-story, 176 unit building on a vacant

Approval of the Preliminary Plan subject

to the noted findings and conditions

lot with parking and landscaping

improvements.

CASE NO./ 22-016MI

PROJECT TYPE: Preliminary Plan Approval

PROJECT 94 Summer Street

LOCATION:


AP 24 Lot 640

C-2 zoning district; Transit

Oriented Development (TOD)

NEIGHBORHOOD: Upper South Providence PROJECT PLANNER: Choyon Manjrekar

RECOMMENDATION:



PROJECT OVERVIEW

The applicant is proposing to construct a five story, 58' tall, 176 unit building providing affordable housing. The subject lot which measures approximately 50,853 SF is currently vacant with frontage on Summer, Conduit and Stewart Streets and Warners Lane. The building will be set to the east, north and west lot lines but set back from the southern lot line to provide parking and a landscaped courtyard. The project will be reviewed as a minor land development project as it involves creation of over 10 dwelling units of housing and over 10,000 SF of gross floor area (GFA) with no commercial development.

ANALYSIS AND IDENTIFICATION OF POTENTIAL ISSUES

<u>Use</u>

The subject lot is zoned C-2 under the TOD overlay, where multifamily development is permitted by right.

Dimensions and site design

The building footprint measures approximately 27,484 SF, resulting in approximately 146,000 SF of GFA and 55% of lot coverage. The building will have a 'C' shaped layout, set to the northern lot line on Conduit Street and the eastern and western wings built to the lot lines on Summer and Stewart Streets. The main entrance will be located on Summer Street, with street access also provided from Stewart Street and Warners Lane. The main lobby, mailroom and office space will be located in the eastern wing. The southern portion of the building will be set back from the southern lot line on Warners Lane, providing space for a landscaped courtyard and parking.

The building's exterior will be composed of light brick, which is permitted by right in the zone. A total of 176 units—all one bedrooms with cooking facilities and bathrooms—will be provided over five stories. The

building's height of approximately 58'2" was determined based on the average grade of the site and is within the 70' height limit of the TOD overlay.

Parking

The TOD overlay does not require parking but 13, 60° angled parking spaces will be provided. The parking area will be accessed from a one-way lane to a drop off area accessed from Stewart Street, which will continue westward to exit onto Summer Street. The applicant will meet the bicycle parking requirement of one space per five dwelling units where 35 spaces are required and 37 will be provided. Twenty nine bicycle parking spaces will be provided south of the vehicular parking area and an additional eight spaces will be provided against the eastern façade.

One loading space is required as the development will provide over 40,000 SF of residential development. An internal loading space providing the minimum requirements of 12' x 35' with a clearance of 15' with access from Summer Street will be provided. The Department of Public Works (DPW) will prohibit parking in front of this space to allow for access to the site. A diagram showing turn radii for different vehicles has been included, which shows that the configuration will allow vehicles to access the loading space and exit the lot without negatively affecting traffic flow.

Landscaping

A landscaped courtyard will be located between the parking area and the southern building face providing open space for the building's residents. The plan will employ a mix of trees, shrubs and grass. The site requires approximately 7,525 SF of canopy coverage but 8,600 SF will be provided. The plan has been approved by the City Forester.

Drainage

Stormwater management measures are required on site as the site measures over 20,000 SF. The site is currently 100% impervious. Best Management Practices (BMP) will include treatment of roof runoff and impervious site areas with sand filters and surge tanks. Treated stormwater will be sent to the sanitary sewer system. Per the stormwater plan, the peak flows will be decreased for one to 100 year storm events. A sediment and erosion control plan outlining measures to prevent runoff from the site during construction has also been submitted.

Public Outreach

The applicant held three community meetings to discuss the project with neighbors and residents.

FINDINGS

Section 806 of the Commission's *Development Review Regulations* requires that the City Plan Commission make the following findings as part of their approval of all land development project applications. Based on the analysis contained herein and subject to the conditions contained in this report, staff has prepared the following findings regarding the request for approval of the Preliminary Plan stage:

1. Consistency—The proposed development is consistent with the Comprehensive Plan and/or has satisfactorily addressed the issues where there may be inconsistencies.

According to the future land use map of *Providence Tommorow: The Comprehensive Plan* this area is intended for Neighborhood Commercial/Mixed Use development, where multifamily development is encouraged, particularly in proximity to commercial corridors. Provision of affordable housing would conform to objectives H-2, H-3 and H-4 of the plan which support creation of new and affordable housing for special populations. Construction of dense development within a single building is in conformance with objective BE-3 of the plan which promotes compact urban development. The parking reduction due to the TOD overlay conforms to objectives M-2, M-3 and M-4 of the plan which promotes use of alternative transportation including biking, transit and walking.

Compliance with Zoning Ordinance—The proposed development is in compliance with the standards and provisions of the Zoning Ordinance.

Use: Multifamily housing is permitted by right in the C-2 zone and more so encouraged under the TOD overlay. Dimension and Design: As discussed, the development conforms to the dimensional and design requirements of the C-2 zone. Addition of landscaping and open space will enhance the building's character.

Parking: The applicant will meet the vehicular and bicycle parking requirements.

3. Environmental Impact—There will be no significant environmental impacts from the proposed development as shown on the final plan, with all required conditions for approval.

Per the applicant, the building is enrolled in the National Grid Zero Energy Buildings program. The project will use approximately 46% less energy than required by current energy codes based on energy modeling of the current design. Additionally, the building will use no fossil fuels, with all electric heating, cooling, and hot water systems. It will have a large 270kW rooftop solar array, and will obtain the balance of all electricity from solar with contracts for remote net metering. The efficiency measures will avoid 273 metric tons of CO2 emissions each year.

No negative environmental impacts are expected as the applicant is expected to come into conformance with all applicable environmental regulations.

4. Buildable Lot—The subdivision or development project, as proposed, will not result in the creation of individual lots with such physical constraints to development that building on those lots according to pertinent regulations and building standards would be impracticable.

There are no physical constraints that impact development of this property as the lot conforms to the dimensional requirements of the zoning ordinance and poses no impediments to development.

5. Street Access—All proposed development projects and all subdivision lots shall have adequate and permanent physical access to a public street. Lot frontage on a public street without physical access shall not be considered compliance with this requirement.

Adequate vehicular and pedestrian access is provided from Summer, Stewart and Conduit Streets.

RECOMMENDATION

Based on the foregoing discussion, the CPC should vote to approve the preliminary plan subject to the following conditions:

- 1. The validity of the preliminary plan approval should be extended to one year from the date of recording of the approval letter.
- 2. Final plan approval should be delegated to DPD staff.

DRAWING LIST DRAWING LIST DRAWING LIST ROOF FRAMING PLAN - SUMMER PLUMBING TYPICAL UNIT PLANS A/V COORDINATION PLANS ROOF FRAMING PLAN - SUMMER 2 PLUMBING MECH RM PART PLAN & SCHEMATIC RCP - DETAIL PLANS **ELEVATION DETAIL BUILDING SECTIONS ELEVATION DETAIL** TYPICAL WOOD FRAMING DETAILS WALL SECTIONS TYPICAL WOOD FRAMING DETAILS PLUMBING FIRE SAFING DETAILS EXTERIOR DETAILS TYPICAL WOOD FRAMING DETAILS PLUMBING FIRE SAFING DETAILS TYPICAL WOOD FRAMING DETAILS PLUMBING WATER HEATER PIPING SCHEMATICS 0 - GENERAL P5.0.3 **COVER SHEET** TYPICAL WOOD FRAMING DETAILS \$5.5 P5.0.4 NOTES. ABBREVIATIONS. KEYNOTES 5 - MECHANICAL 7 - FIRE PROTECTION FIRE PROTECTION ABBREVIATIONS & SYMBOLS MECHANICAL ABBREVIATIONS, SYMBOLS, & LEGENDS FP0.0.0 1 - CIVIL FIRE PROTECTION PARTIAL LOWER LVL EAST C0.0 FIRE PROTECTION PARITAL FIRST FLR EAST LIMITED CONTENT BOUNDARY & EXISTING CONDITIONS PLAN • M1.1.1 EXISTING UTILITY PLAN TRADE PARTIAL FIRST FLR WEST SEDIMENT AND EROSION CONTROL AND DEMO PLAN MECHANICAL PARTIAL SECOND FLOOR EAST FIRE PROTECTION PARTIAL SECOND FLR EAST PROPOSED SITE PLAN MECHANICAL PARTIAL SECOND FLOOR WEST PROPOSED UTILITY PLAN PROPOSED GRADING PLAN FIRE PROTECTION PARTIAL THIRD FLR WEST FIRE PROTECTION PARTIAL FOURTH FLR EAST PROPOSED LANDSCAPE PLAN MECHANICAL PARTIAL FOURTH FLOOR EAST FIRE PROTECTION PARTIAL FOURTH FLR WEST **DETAILS & NOTES** FIRE PROTECTION PARTIAL FIFTH FLR EAST **DETAILS & NOTES** FIRE PROTECTION PARTIAL FIFTH FLR WEST **DETAILS & NOTES** FIRE PROTECTION PARTIAL ROOF PLAN EAST C2.5 DETAILS & NOTES MECHANICAL PARTIAL FIRST FLOOR EAST FP2.6.2 FIRE PROTECTION PARTIAL ROOF PLAN WEST 2 - LANDSCAPE FP3.0.1 FIRE PROTECTION STAIR RISERS F5.0.1 SITE PLAN LANDSCAPE MECHANICAL PARTIAL SECOND FLOOR EAST FIRE PROTECTION TYPICAL DETAILS FP5.0.2 L3.1.5 MECHANICAL PARTIAL SECOND FLOOR WEST FIRE PROTECTION FIRE SAFING DETAILS FP5.0.3 L5.7 FIRE PROTECTION SCHEDULES 3 - ARCHITECTURAL MECHANICAL PARTIAL THIRD FLOOR WEST 8 - ELECTRICAL MECHANICAL PARTIAL FOURTH FLOOR EAST BASEMENT & FIRST FLOOR KEY PLANS BASEMENT POWER AND LIGHTING PLAN SECOND & THIRD FLOOR KEY PLANS SUMMER 1 FIRST FLOOR POWER PLAN FOURTH & FIFTH FLOOR KEY PLANS SUMMER 1 SECOND FLOOR POWER PLAN FIRST FLOOR PLAN - SUMMER 1 SUMMER 2 SECOND FLOOR POWER PLAN FIRST FLOOR PLAN - SUMMER 2 SUMMER 2 THIRD FLOOR POWER PLAN MECHANICAL TYPICAL UNIT PLANS SECOND FLOOR PLAN - SUMMER 2 SUMMER 1 FOURTH FLOOR POWER PLAN RCP - BASEMENT & PENTHOUSE MECHANICAL TYPICAL UNIT PLANS MECHANICAL OFFICE AREA PARTIAL PLANS RCP- TYP. UPPER FLOOR - SUMMER 2 M2.5.0 MECHANICAL DETAILS SUMMER 2 ROOF POWER AND LIGHTING PLAN **ELEVATIONS** MECHANICAL SCHEDULES M2.8.0 • E2.1.2 SUMMER 2 FIRST FLOOR LIGHTING PLAN MECHANICAL SCHEDULES BUILDING SECTION SUMMER 1 SECOND FLOOR LIGHTING PLAN 6 - PLUMBING SUMMER 1 THIRD FLOOR LIGHTING PLAN WALL SECTIONS PLUMBING SYMBOLS & ABBREVIATION E2.3.1 EXTERIOR DETAILS PLUMBING LOWER LVL EAST - W&V SUMMER 2 THIRD FLOOR LIGHTING PLAN E2.3.2 UNIT ELEVATIONS & DETAIL PLAN INTERIOR ELEVATIONS PLUMBING FIRST FLR EAST - W&V SUMMER 2 FOURTH FLOOR LIGHTING PLAN E2.4.2 STAIR ELEVATIONS & DETAIL PLANS SUMMER 1 FIFTH FLOOR LIGHTING PLAN TRADE FIRST FLR WEST - W&V STAIR ELEVATIONS & DETAIL PLANS PLUMBING SECOND FLR EAST - W&V E2.5.2 STAIR ELEVATIONS & DETAIL PLANS PLUMBING SECOND FLR WEST - W&V ONE-LINE POWER RISER DIAGRAM € E4.1 **ELEVATOR ELEVATIONS & DETAIL PLANS** WIRING SCHEMATICS AND DETAILS E4.2 ● E5.1 SCHEDULES INTERIOR DETAILS E5.2 SCHEDULES PLUMBING FOURTH FLR EAST - W&V E5.3 SCHEDULES A8.1 DOOR SCHEDULE PLUMBING FIFTH FLR EAST - W&V E5.4 SCHEDULES WINDOW SCHEDULE PLUMBING FIFTH FLR WEST - W&V E5.5 SCHEDULES 4 - STRUCTURAL PLUMBING ROOF PLAN EAST - W&V 9 - FIRE ALARM STRUCTURAL COVER SHEET PLUMBING ROOF PLAN WEST - W&V ◆ FA1.0 BASEMENT FIRE ALARM PLAN S0.00 SUMMER 1 FIRST FLOOR FIRE ALARM PLAN PLUMBING PARTIAL LOWER LVL EAST - H&CW • FA1.1.1 LATERAL FORCE RESISTING SYSTEM & DESIGN CRITERIA PLUMBING LOWER LVL WEST - H&CW FA1.1.2 SUMMER 2 FIRST FLOOR FIRE ALARM PLAN PLUMBING FIRST FLR EAST - H&CW SUMMER 1 SECOND FLOOR FIRE ALARM PLAN FA1.2.2 SUMMER 2 SECOND FLOOR FIRE ALARM PLAN PLUMBING FIRST FLR WEST - H&CW FA1.3.1 SUMMER 1 THIRD FLOOR FIRE ALARM PLAN **BASEMENT FOUNDATION PLAN - SUMMER 1** PLUMBING SECOND FLR EAST - H&CW • FA1.3.2 SUMMER 2 THIRD FLOOR FIRE ALARM PLAN BASEMENT FOUNDATION PLAN - SUMMER 2 PLUMBING SECOND FLR WEST - H&CW BASEMENT FOUNDATION PLAN PLUMBING THIRD FLR EAST - H&CW OVERALL 3D VIEWS - THIRD & FOURTH FLOOR PLUMBING THIRD FLR WEST - H&CW OVERALL 3D VIEWS - FIFTH FLOOR & ROOF PLUMBING FOURTH FLR EAST - H&CW PLUMBING FOURTH FLR WEST - H&CW LEVEL 5 FRAMING PLAN PLUMBING FIFTH FLR EAST - H&CW ROOF FRAMING PLAN PLUMBING FIFTH FLR WEST - H&CW PENTHOUSE ROOF FRAMING PLAN PLUMBING ROOF PLAN EAST - H&CW

PLUMBING ROOF PLAN WEST - H&CW

PLUMBING TYPICAL UNIT PLANS

BASEMENT AND FIRST FLOOR FOUNDATION OVERALL PLANS • P3.6.2

SECOND AND THIRD FLOOR OVERALL FRAMING PLAN

FOURTH AND FIFTH FLOOR OVERALL FRAMING PLAN

ROOF OVERALL FRAMING PLAN

SECOND FLOOR FRAMING PLAN - SUMMER 1
SECOND FLOOR FRAMING PLAN - SUMMER 2
THIRD FLOOR FRAMING PLAN - SUMMER 1
THIRD FLOOR FRAMING PLAN - SUMMER 2

FOURTH FLOOR FRAMING PLAN - SUMMER 1 FOURTH FLOOR FRAMING PLAN - SUMMER 2 FIFTH FLOOR FRAMING PLAN - SUMMER 1

S2.2.3 - ALT FOUNDATION PLAN OPTIONS

• S2.2.13 FIFTH FLOOR FRAMING PLAN - SUMMER 2

S2.2.3

		SUMMER I			
		DWELLING UNIT DISTRIBUT	TION		
LEVEL		AVERAGE NSF		# of Units	# of Type A
0	1BR / 1BA	0	NSF	0	0
1	1BR / 1BA	509	NSF	13	2
2	1BR / 1BA	513	NSF	18	4
3	1BR / 1BA	512	NSF	18	4
4	1BR / 1BA	512	NSF	20	4
5	1BR / 1BA	513	NSF	18	4
TOTAL				87	18
	S	QUARE FOOTAGE BREAK	DOWN		l
RESIDENT	IAL	NON-RESIDENTIAL PROG	RAM AREA	CON	MON
49,168	GSF	4,310	GSF	18,967	GSF

		SUMMER	I		
		DWELLING UNIT DIST	RIBUTION		
LEVEL		AVERAGE	NSF	# of Units	# of Type A
0	1BR / 1BA	0	NSF	0	0
1	1BR / 1BA	513	NSF	15	2
2	1BR / 1BA	512	NSF	19	4
3	1BR / 1BA	512	NSF	19	4
4	1BR / 1BA	511	NSF	17	4
5	1BR / 1BA	511	NSF	19	4
TOTAL				89	18
	S	L QUARE FOOTAGE BR	EAKDOWN		<u> </u>
RESIDENTIAL		NON-RESIDENTIAL PROGRAM AREA		COMMON	
54,087 GSF			5,234 GSF	12.088	GSF

ALL UNITS ARE TYPE B ADAPTABLE UNLESS INDICATED AS TYPE A ACCESSIBLE

SUMMER STREET APARTMENTS

PROGRESS SET

02.18.2022

Owner

SUMMER STREET LP1/SUMMER STREET LP2

Architect:


KITE Architects Inc. One Central Street, Providence, RI 02907 401.272.0240 info@kitearchitects.com

Contractor:

TBD



PROJECT NAME:	94 SUMMER ST	94 SUMMER STREET (SUMMER I & SUMMER II)				
PROJECT ADDRESS:	94 SUMMER ST	REET, PROVIDENCE RHODE ISLA	ND 02907			
PARCEL DATA:	PLAT: 24 LOT:	640				
PARCEL AREA:	50,165 SF					
CLIENT NAME:	SUMMER STRE	ET LP1/SUMMER STREET LP2				
CLIENT ADDRESS:	160 BROAD STE	REET, PROVIDENCE RI 02907				
BUILDING TYPE:	TYPE III B / TYP	PE III(200)				
BUILDING SIZE:	143,854 GSF TC	OTAL; 48,000 GSF MAX PER FLOOI	R			
DESCRIPTION OF WORK:	NEW CONSTRU	ICTION 5 STORIES ABOVE GRADE	E & PARTIAL BASEMENT			
	ZC	ONING DATA				
ZONING ORDINANCE:	CITY OF PROVI	DENCE ZONING ORDINANCE, API	RIL 6, 2020			
ZONING DISTRICT:	C2 TRANSIT OF	RIENTED DEVELOPMENT OVERLA	ΛY			
DATA:	REFERENCE	REQUIRED / ALLOWABLE	PROPOSED / EXISTING			
USE:	SEC. 501	MULTI-FAMILY RESIDENTIAL PERMITTED BY RIGHT	MULTI-FAMILY AND PROPOSED			
DWELLING UNITS ALLOWED)	NO MAXIMUM	176			
LOT FRONTAGE:	SEC. 502	NONE	0'-0"			
MIN. LOT AREA:	SEC. 502	NONE	+/- 14,219 SF			
BUILDING HEIGHT:	SEC. 502	70'-0"	58'-2"			
PARKING:	SEC. 502	0 REQUIRED	13			
PARKING RATIO:	'	0 REQUIRED	13 PARKING / 176 UNITS = 0.074			
FRONT SETBACK:	SEC. 502	60% WITHIN BUILD TO ZONE TO ≤ 5'-0"	68.7% WITHIN BUILD-TO ZONE<5'-0"			
SIDE SETBACK:	SEC. 502	40% WITHIN BUILD TO ZONE TO ≤ 5'-0"	43.2% WITHIN BUILD-TO ZONE<5'-0"			
REAR SETBACK:	SEC. 502	NONE REQUIRED	0'-0"			
% OF TRACT OCCUPIED BY	BUILDING		25,867 SF = 51%			
% OF BUILDING OCCUPIED	11,748 SF = 23%					
% OF TRACT OCCUPIED BY	12,550 SF = 26%					



kite

KITE Architects, Inc.
One Central Street
Providence, Rhode Island 02907
401 272.0240
info@kitearchitects.com

CIVIL ENGINEER NARRAGANSETT ENGINEERING INC. 3102 East Main Rd, Portsmouth, RI 02871

STRUCTURAL ENGINEER ODEH ENGINEERS 1223 Mineral Spring Ave, North Providence, RI 02904

MECHANICAL ENGINEER
WILKINSON ASSOCIATES
615 Jefferson Blvd, Warwick, RI 02886

ELECTRICAL ENGINEER

STERLING ENGINEERING CO. INC. 79 Main St, Sturbridge, MA 01566

LANDSCAPE ARCHITECT
ANJALI JOSHI DESIGN
161 Exchange St, Pawtucket, RI 02860

NOT FOR CONSTRUCTION

PROGRESS SET

02.18.2022

SUMMER STREET APARTMENTS

94 Summer Street, Providence, RI 02903

PROJECT NO.

NO. DATE ISSUED FOR

12/17/21 PROGRESS SET

02/18/22 PROGRESS SET

COVER SHEET

© COPYRIGHT2022 KITE ARCHITECTS,

A0.0





STREET VIEW

94 SUMMER STREET APARTMENTS

kite architects one central street providence, rhode island 02907 401 272 0240 kitearchitects.com © copyright 2022 kite architects, inc. unauthorized use is strictly prohibited

No. CPC

PROJECT No. 2032 DATE: 03.25.22





COURTYARD VIEW

94 SUMMER STREET APARTMENTS

kite architects one central street providence, rhode island 02907 401 272 0240 kitearchitects.com © copyright 2022 kite architects, inc. unauthorized use is strictly prohibited

No. CPC.

PROJECT No. 2032 DATE: 03.25.22



Plant List: KEY QTY	BOTANICAL NAME	COMMON NAME	NATIVE	SIZE	NOTE
				U.L.L	
-	NEW PLANTING ON STREET SIDE WALK +CMW PF	REMISES			
<u>rees</u>	TREES - Flowering			0111	Volland Fall Calandonian flavores
	5 Acer Campestre or Prunus sargentii	Campestre Maple or flowering cherr	У	2"cal	Yellow Fall Color /Spring flowers
	5 Nyssa sylvatica Wildfire/JFS Red Firestarter	Black Gum	Y	2"cal	
	3 Amelanchier arborea 'Robin Hill'	Serviceberry/Shabush	Υ	8' b&b	Multistemstem 1-1.5"cal
	II Juniper Virginiana Emerald Sentinel	Eastern red cedar -15' high		6' b&b	
	SHRUBS				
Shrubs/Small Trees	Hamamalis xinteremedia 'Jelena'	Winter blooming Witchazel	N	4/5'b&b	
	Itea henry's garnet	Itea	Υ	#5	
	llex Glabra	Inkberry	Υ	# 5	Evergreen screen
	PERENNIALS	·			
Perennials_	Amsonia hubertii			1 gal	2-3' H, 2-3' Spread
	Carex pensylvanica	Sedge	Υ	4" plugs	•
	Drypoteris ferns	Autumn Fern		1 gal	
	Eupotorium purpureum ssp macultatum gateway	Joe Pye weed	Υ	1 gal	5/6' H, 3-5' Spread, 24" spacing
	Liriope varieagated	,		1 gal	
	Monarda didyma 'Jacob cline'	Bee balm	Υ	3	
	Panicum virgatum		Υ	1 gal	3-4' H, 2-3'Spread, 12" spacing
	Penestemon Husker red		-	1 ga;	o i ii, ii o opioala, iii opalaliig
	Vinca	Evergreen Grouncover		Flat	
/ines_	4 Hydrangea anomala petiolaris 'Miranda'	Climbing hydrangea		#2 stkd	
Greenscreen	r riyarangea anomala peticians winanda			"Z Stra	
<u> yr ceriser cerr</u>					
	EXISTING STREET TREES				
	TREES - Street trees				
	3 Acer Campestre	Campestre Maple	Υ	2"cal	Yellow Fall Color
	7 Nyssa sylvatica Wildfire/JFS Red Firestarter	Black Gum	Υ	2"cal	
	Tree wite				
	Tree pits 2 No mow grass and groundcovers				4"-12" Ground cover



ALL TREES ON SITE ARE INVASIVE AND ARE RECOMMENDED TO BE



1000 SQFT

MEDIUM TREE

700 SQFT

KITE Architects, Inc. Providence, Rhode Island 02907 401 272.0240 info@kitearchitects.com

CIVIL ENGINEER NARRAGANSETT ENGINEERING INC. 3102 East Main Rd, Portsmouth, RI 02871

STRUCTURAL ENGINEER ODEH ENGINEERS

1223 Mineral Spring Ave, North Providence,

RI 02904

MECHANICAL ENGINEER WILKINSON ASSOCIATES

615 Jefferson Blvd, Warwick, RI 02886

ELECTRICAL ENGINEER STERLING ENGINEERING CO. INC. 79 Main St, Sturbridge, MA 01566

LANDSCAPE ARCHITECT

161 Exchange Street Pawtucket, RI 02860

ANJALI JOSHI DESIGN

NOT FOR

CONSTRUCTION

02.18.2022

PROGRESS SET


SUMMER STREET APARTMENTS

94 Summer Street, Providence, RI 02903 PROJECT NO.

NO. DATE ISSUED FOR 3/25/2022 PROGRESS SET

© COPYRIGHT KITE ARCHITECTS, INC UNAUTHORIZED USE IS STRICTLY PROHIBITED

LA. 3.1



kite

KITE Architects, Inc.
One Central Street
Providence, Rhode Island 02907
401 272.0240
info@kitearchitects.com

CIVIL ENGINEER
NARRAGANSETT ENGINEERING INC.
3102 East Main Rd, Portsmouth, RI 02871

STRUCTURAL ENGINEER
ODEH ENGINEERS
1223 Mineral Spring Ave, North Providence,
RI 02904

WILKINSON ASSOCIATES 615 Jefferson Blvd, Warwick, RI 02886

ELECTRICAL ENGINEER STERLING ENGINEERING CO. INC. 79 Main St, Sturbridge, MA 01566

MECHANICAL ENGINEER

LANDSCAPE ARCHITECT ANJALI JOSHI DESIGN 161 Exchange St, Pawtucket, RI 02860

NOT FOR CONSTRUCTION

PROGRESS SET

02.18.2022

SUMMER STREET APARTMENTS

94 Summer Street, Providence, RI 02903

PROJECT NO.

NO. DATE ISSUED FOR

12/17/21 PROGRESS SET

02/18/22 PROGRESS SET

FLOOR PLANS:

© COPYRIGHT 2022 KITE ARCHITECTS, INC UNAUTHORIZED USE IS STRICTLY PROHIBITED

FIRST FLOOR

NOT FOR CONSTRUCTION

A2.2.0

KITE Architects, Inc. One Central Street Providence, Rhode Island 02907 401 272.0240

info@kitearchitects.com

CIVIL ENGINEER NARRAGANSETT ENGINEERING INC. 3102 East Main Rd, Portsmouth, RI 02871

STRUCTURAL ENGINEER **ODEH ENGINEERS** 1223 Mineral Spring Ave, North Providence, RI 02904


MECHANICAL ENGINEER WILKINSON ASSOCIATES 615 Jefferson Blvd, Warwick, RI 02886

ELECTRICAL ENGINEER STERLING ENGINEERING CO. INC. 79 Main St, Sturbridge, MA 01566

LANDSCAPE ARCHITECT ANJALI JOSHI DESIGN 161 Exchange St, Pawtucket, RI 02860

NOT FOR CONSTRUCTION PROGRESS SET

02.18.2022



SUMMER STREET **APARTMENTS**


94 Summer Street, Providence, RI 02903 PROJECT NO.

> NO. DATE ISSUED FOR 12/17/21 PROGRESS SET 02/18/22 PROGRESS SET


ROOF PLAN


© COPYRIGHT2022 KITE ARCHITECTS, INC UNAUTHORIZED USE IS STRICTLY PROHIBITED

A2.2.3



A3.1





Providence, Rhode Island 02907

Providence, Rhode Island 02907

12.17.21 PROGRESS SET

A1.0

SHEET INDEX:

1- SV1.0: LIMITED CONTENT BOUNDARY AND EXISTING CONDITIONS

2- SV1.1: EXISTING UTILITY PLAN

3- SV1.2: SEDIEMNT AND EROSION CONTROL AND DEMO PLAN

4- C1.0: PROPOSED SITE PLAN

5- C1.1: PROPOSED UTILITY PLAN

6- C1.2: PROPOSED GRADING PLAN

7- C2.1: DETAILS & NOTES

8- C2.2: DETAILS & NOTES 9- C2.3: DETAILS & NOTES

10- C2.4: DETAILS & NOTES

11- C2.5: DETAILS & NOTES

SUMMER STREET APARTMENTS

COVER SHEET

MINOR LAND DEVELOPMENT APPLICATION

OWNER OF RECORD:

CROSSROADS RI (PER ASSESSOR)

APPLICANT:

CROSSROADS RI

PREPARED BY:


NARRAGANSETT ENGINEERING INC.

3-25-22

1

EXTENDED SITE VIEW

GIS ZONING MAP



Zoning notes:

Zone: C-2 (Gen Commercial) / TOD (Traffic Sensitive Overlay District)

See architectural plans by Kite Architects for all zoning (parking, bike spaces, loading areas, etc.) data unless noted otherwise:

Selected zoning data:


One Loading Space Required, One Provided. 1406.B - Loading Space 12'x35'x15' (height)

1407.A


2. Multi-Family and Rowhouse Dwellings, and


Non-Residential Driveways With the exception of loading berths, driveways are limited to a maximum width of 12 feet for oneway drives, and a maximum of 24 feet for two-way drives.








3/25/22 DP



















GENERAL NOTES:


- THE STATE OF RHODE ISLAND STANDARD SPECIFICATION FOR ROAD AND BRIDGE CONSTRUCTION, 2004 EDITION, AND THE RHODE ISLAND STANDARD DETAILS ARE MADE A PART HEREOF AS FULLY AND COMPLETELY AS IF ATTACHED HERETO. ALL WORK SHALL CONFORM TO RHODE ISLAND STANDARD SPECIFICATION FOR ROAD AND BRIDGE CONSTRUCTION 2004 EDITION OR LATEST REVISION. THE 2004 EDITION OF THE STANDARD SPECIFICATION MAY BE OBTAINED AT THE RHODE ISLAND DEPARTMENT OF TRANSPORTATION.
- 2. IT SHALL BE THE CONTRACTOR'S SOLE RESPONSIBILITY TO APPLY FOR AND OBTAIN ANY AND ALL NECESSARY PERMITS, PAY ALL FEES AND POST ALL BONDS ASSOCIATED WITH THE SAME, AND COORDINATE WITH ARCHITECT OR ENGINEER AS NECESSARY
- 3. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR THE SAFETY OF THE JOB SITE. THE CONTRACTOR SHALL PROVIDE TEMPORARY FENCING AND/OR BARRIERS AROUND ANY EXPOSED EXCAVATED AREAS IN ACCORDANCE WITH OSHA STANDARDS.
- IN THE CASE THAT ANY DEVIATION / ALTERATION / OR IMPROVEMENT FROM THE APPROVED PLANS IS NECESSARY THE CONTRACTOR SHALL IMMEDIATELY CONTACT THE ENGINEER AND OWNER PRIOR TO OCCURRENCE OF DEVIATION
- 5. ALL WORK SHALL BE LIMITED TO THE AREAS WITHIN THE LIMIT OF DISTURBANCE DISPLAYED ON THESE PLANS OR PROPERTY LINE IF LIMIT OF DISTURBANCE IS UNCLEAR. ANY AREA DISTURBED OUTSIDE OF THE LIMIT OF DISTURBANCE SHALL BE REPAIRED AND RESTORED TO ITS ORIGINAL CONDITION AT NO COST TO THE OWNER OR ENGINEER, AND PREFORMED TO THE ENGINEERS SATISFACTION
- ALL SITE WORK SHALL MEET OR EXCEED THE SITE WORK SPECIFICATION SHOWN ON THESE PLANS AND/OR ACCOMPANYING SPECIFICATIONS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING IF ANY CONFLICTS WITH EXISTING CONDITIONS OR PROPOSED CONDITIONS EXIST. IF ANY CONFLICTS ARE DISCOVERED, THE CONTRACTOR SHALL NOTIFY THE OWNER AND ENGINEER PRIOR TO INSTALLATION OF ANY PORTION OF THE SITE WORK THAT WOULD BE AFFECTED
- 7. EXCAVATED ROCK SHALL BE REMOVED FROM THE SITE AND LEGALLY DISPOSED OF UNLESS OTHER ARRANGEMENTS ARE MADE WITH THE OWNER, SUITABLE ROCK MAY BE UTILIZED IN FILL AREAS WITH WRITTEN PERMISSION OF THE OWNERS REPRESENTATIVES
- 8. DEBRIS, ORGANICS AND OTHER UNSUITABLE MATERIALS UNCOVERED DURING THE COURSE OF SITE EXCAVATION SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY
- 9. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR MAINTAINING THE INTEGRITY OF ALL EXISTING UTILITIES THAT SERVICE THE SITE AND NEIGHBORING AREAS. IF ANY DAMAGE OCCURS TO EXISTING UTILITIES IT SHALL BE THE CONTRACTORS RESPONSIBILITY TO PAY ALL COSTS ASSOCIATED WITH REPAIR OF UTILITIES AS DIRECTED BY THE ENGINEER, UTILITY OWNER, OR GOVERNING AGENCY
- 10. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR QUANTITY TAKE-OFF IN COMPUTING ANY ESTIMATES
- 11. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ESTABLISHING AND MAINTAINING ALL TEMPORARY SEDIMENTATION AND EROSION CONTROLS.
- 12. THE LOCATION OF EXISTING UTILITIES AS SHOWN ARE APPROXIMATE AND SHALL BE VERIFIED BY THE CONTRACTOR. "DIG SAFE" SHALL BE CONTACTED BY THE CONTRACTOR AS PART OF THIS VERIFICATION
- 13. NO EXCAVATION SHALL PROCEED UNTIL UTILITY COMPANIES ARE NOTIFIED IN ADVANCE
- 14. ALL TREE PROTECTION BY OTHERS UNLESS OTHERWISE NOTED
- 15. CONTRACTOR TO LOAM AND SEED ALL DISTURBED AREAS WITH APPROPRIATE SEED MIXTURES

GRADING AND UTILITIES NOTES:


- 1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THAT THE PROPOSED WORK SHOWN ON THESE PLANS DO NOT CONFLICT WITH ANY EXISTING CONDITIONS OR OTHER PROPOSED WORK. IF CONFLICTS ARISE, THE CONTRACTOR SHALL NOTIFY THE OWNER AND ENGINEER PRIOR TO INSTALLATION OF ANY PORTION OF THE SITE WORK WHICH WOULD BE AFFECTED. NO FIELD ADJUSTMENTS IN THE LOCATION OF SITE ELEMENTS SHALL BE MADE WITHOUT THE ENGINEERS APPROVAL
- WHERE AN EXISTING UTILITY IS FOUND TO CONFLICT WITH WORK, THE LOCATION, ELEVATION, SIZE AND MATERIAL SHALL BE ACCURATELY DETERMINED BY THE CONTRACTOR IMMEDIATELY AND THE INFORMATION FURNISHED TO THE ENGINEER FOR RESOLUTION. THE CONTRACTOR SHALL NOT CONTINUE WORK ON AFFECTED UTILITIES UNTIL THE CONFLICT IS RESOLVED
- 3. ALL WORK PERFORMED AND ALL MATERIALS FURNISHED SHALL CONFORM WITH THE LINE AND GRADES ON THE PLANS AND SITE WORK SPECIFICATIONS
- 4. AT ALL LOCATIONS WHERE EXITING CURBING OR PAVEMENT ABUT NEW CONSTRUCTION, THE EDGE OF THE EXISTING CURB OR PAVEMENT SHALL BE SAW CUT TO A CLEAN, SMOOTH EDGE. BLEND NEW PAVEMENT AND CURBS SMOOTHLY INTO EXISTING BY MATCHING LINES, GRADES AND JOINTS
- 5. ALL UTILITY COVERS, GRATES, AND THE LIKE SHALL BE BE FLUSH WITH THE SURROUNDING SURFACE OR PAVEMENT FINISH. RIM ELEVATIONS ARE APPROXIMATE AND FINAL ELEVATIONS ARE TO BE SET FLUSH AND CONSISTENT WITH GRADING
- 6. THE CONTRACTOR SHALL MAKE ALL ARRANGEMENTS FOR THE ALTERATION OF PRIVATE UTILITIES BY THE UTILITY COMPANY, AS REQUIRED.
- 7. THE CONTRACTOR SHALL PROTECT ALL UNDERGROUND UTILITY FACILITIES FROM EXCESSIVE VEHICULAR LOADING. ANY DAMAGE RESULTING TO THESE FACILITIES SHALL BE RESTORED TO THEIR ORIGINAL CONDITION AT THE CONTRACTORS EXPENSE
- 8. ALL WATER WORKS SHALL HAVE 5 FEET OF COVER
- 9. GAS, ELECTRIC, AND COMMUNICATIONS ROUTING ARE SUBJECT TO REVIEW AND APPROVAL BY UTILITY COMPANY
- 10. DURING CONSTRUCTION CONTRACTOR SHALL PROTECT EXITING UTILITIES BY PROVIDING TEMPORARY SUPPORTS OR SHEETING AS REQUIRED AT NOT ADDITIONAL COST TO THE OWNER
- 1. EXCAVATION REQUIRED WITHIN THE PROXIMITY OF EXISTING UTILITY LINES SHALL BE DONE BY HAND. CONTRACTOR SHALL REPAIR ANY DAMAGE TO EXISTING UTILITY LINE OR STRUCTURES INCURRED DURING CONSTRUCTION OPERATION AT NO COST TO THE OWNER
- 12. PITCH EVENLY BETWEEN ALL SPOT GRADES.
- 13. THE CONTRACTOR IS RESPONSIBLE FOR REMOVAL AND DISPOSAL OF ANY, ROCKS,
- DEBRIS, ORGANICS, OR THE LIKE UNCOVERED IN THE COURSE OF WORK







7" N.T.S.



ISSUE DATE: 1/6/17

Narragansett
Engineering Inc.
Civil - Survey Structural Environmental Design
3102 East Main Road, Portsmouth RI 02871
Tel. 401.683.6630 www.nei-cds.com

SHEET TITLE
DETAILS & NOTES

SUMMER STREET APARTMENTS

IN CARE OF: CHRISTINE M. WEST, AIA | PRINCIPAL KITE ARCHITECTS | ONE CENTRAL STREET | PROVIDENCE RI 02907 KITEARCHITECTS.COM | 401.272.0240 X117 CW@KITEARCHITECTS.COM

PROPERTY RECORD

94 SUMMER ST, PROVIDENCE, RI 02903


PLAT: 24, LOT: 640

ZONE: C-2

AREA: 1.16 ACRES


N/F: CROSSROADS RI

REF. NEI # 0019.198



	<u> </u>	0.00111			
PROJECT #		DATE	DRAWN	CHECK	
21.0103		12/17/21	LD	NKH	
No	DATE	REVISIONS/DESCRIPTION			BY
1	02/18/22	PROGRESS S	SET		СВ
	1				

DRAWINGS MUST BE PRINTED IN COLOR TO BE VALID THIS NOTE SHOULD BE BLUE. IF THIS NOTE IS NOT BLUE, PLEASE REPRINT IN COLOR OR CONTACT NEI



<u>NOTES</u>

ISSUE DATE: 1/6/17


- SHALL BE IN ACCORDANCE WITH SECTION 905 OF THE R.I. STANDARD SPECIFICATIONS.
 SEE CURB SETTING DETAIL WHERE APPLICABLE.
- 3. RUNNING SLOPE OF SIDEWALK SHALL NOT EXCEED 8.3% (1:12). TYPICALLY, RUNNING SLOPE SHALL MATCH ROAD SLOPE.
- SLOPE SHALL MATCH ROAD SLOPE.


 4. CROSS SLOPE OF SIDEWALK SHALL NOT EXCEED 2% (1:50).
- 5. SIDEWALK MAY BE SUBJECT TO GRASS STRIP INSTALLATION. CONSULT WITH DPW ENGINEERING
- 6. GRAVEL BORROW BASE SHALL COMPACT TO ACHEIVE SOIL DENSITY VALUES OF 95% MODIFIED PROCTOR DENSITY (AASHTO T180).7. SIDEWALK REPAIRS TWENTY FEET OR LONGER ARE SUBJECT TO REQUIREMENTS HEREIN.
- SIDEWALK REPAIRS SHORTER THAN TWENTY FEET SHALL MAKE EVERY EFFORT TO MEET REQUIRED SLOPES.

 8. CONTROLL JOINTS SHALL BE INSTALLED EVERY 5 FEET IN EACH DIRECTION.
- 9. EXPANSION JOINTS SHALL BE INSTALLED EVERY 5 FEET IN EACH DIRECTION.

 9. EXPANSION JOINTS SHALL BE INSTALLED EVERY 20 FEET IN EACH DIRECTION AT FOUNDATIONS AND WALLS AND IN A SQUARE PATTERN AROUND MANHOLE COVERS, HYDRANTS, SIGN POSTS AND UTILITY POLES. THE EXPANSION JOINT SHALL BE THE FULL DEPTH OF THE SIDEWALK AND FILLED WITH AN APPROVED TYPE OF PREMOLDED EXPANSION JOINT FILLER.







FINISHED GRADE

- 1. WHERE IT IS NOT POSSIBLE TO MAINTAIN A 10 FOOT HORIZONTAL SEPARATION, A DEVIATION MAY BE GRANTED ON A CASE-BY-CASE BASIS. SUCH DEVIATION MAY ALLOW INSTALLATION OF THE SEWER CLOSER TO A WATER SERVICE, PROVIDED THAT:
- A.) THE SEWER LINE AND WATER SERVICE ARE LAID IN SEPARATE TRENCHES AND THE CROWN OF THE SEWER LINE SHALL BE AT LEAST 18 INCHES BELOW THE BOTTOM OF THE WATER SERVICE.
- B.) THE SEWER LINE AND WATER SERVICE MAY BE INSTALLED IN THE SAME TRENCH WITH THE WATER SERVICE PLACED ON A BENCH OF UNDISTURBED EARTH AND THE CROWN OF THE SEWER LINE SHALL BE AT LEAST 18 INCHES BELOW THE BOTTOM OF THE WATER SERVICE.
- 2. IN CASES WHERE IT IS IMPOSSIBLE TO OBTAIN PROPER HORIZONTAL AND VERTICAL SEPARATION AS STIPULATED ABOVE (INCLUDING CROSSING OVER), THE FOLLOWING PROTECTION SHALL BE PROVIDED:
- A.) ENCASEMENT OF THE SEWER PIPE IN CONCRETE WITH A MINIMUM THICKNESS OF 6" IN ALL DIRECTIONS AROUND THE OUTSIDE OF THE PIPE EXTENDING TO A DISTANCE THAT WILL PROVIDE THE REQUIRED 10 FEET HORIZONTAL OR 18 INCH VERTICAL SEPARATION BETWEEN THE UNENCASED PORTIONS OF THE PIPES. THE WATER MAIN SHALL BE ENCASED IN EXCAVATABLE CONTROLLED LOW STRENGTH MATERIAL (CLSM) CONFORMING WITH RIDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION SECTION 603.
- B.) PLACING EITHER THE SEWER LINE OR WATER SERVICE IN A WATERTIGHT CARRIER PIPE EXTENDING TO A DISTANCE THAT WILL PROVIDE THE REQUIRED 10 FEET HORIZONTAL OR 18 INCH VERTICAL SEPARATION BETWEEN THE UNENCASED PORTIONS OF THE PIPES.
- 3. FOR ALL CROSSINGS, ANY NEW WATER LINES SHALL BE LAID WITH A FUL LENGTH OF WATER PIPE CENTERED AT THE POINT OF CROSSING. THERE SHALL BE NO JOINTS PERMITTED AT THE POINT OF CROSSING.
- 4. FOR ANY CROSSING OF A WATER MAIN BELOW AN EXISTING OR PROPOSED SANITARY SEWER LINE, ADEQUATE STRUCTURAL SUPPORT MUST BE PROVIDED FOR THE SANITARY LINE IN ORDER TO PREVENT SETTLING




TABLE 1: 4" THRU 10" FITTINGS				TABLE	2: 12" T	HRU 16"	FITTINGS		
SOIL TYPE	TE	ES	BENDS		SOIL TYPE	TE	ES	BE	NDS
SOIL TIPE	Α	В	Α	В	1 SOIL TIPE	Α	В	Α	В
SOFT CLAY	48"	24"	48"	24"	SOFT CLAY	60"	36"	72"	36"
SAND	24"	24"	24"	24"	SAND	36"	30"	48"	30"
GRAVEL	24"	18"	24"	18"	GRAVEL	30"	24"	40"	24"


- 1. CONCRETE FOR ALL THRUST BLOCKS TO BE MINIMUM 3,000 PSI., 28 DAY STRENGTH, TYPE I CEMENT, 3/4" STONE.
- 2. WHERE POSSIBLE, CONSTRUCT THRUST BLOCKS AGAINST UNDISTURBED SOIL. WHERE NOT POSSIBLE PLACE FILL BETWEEN THE THRUST BLOCK AND THE UNDISTURBED SOIL COMPACTED TO 90% STANDARD PROCTOR
- 3. WRAP FITTINGS WITH POLYETHYLENE PRIOR TO CONSTRUCTING THRUST BLOCKS. NO JOINTS SHALL BE COVERED WITH CONCRETE.
- 4. THRUST BLOCK DIMENSIONS ARE BASED ON A MAXIMUM WATER MAIN PRESSURE OF 150 PSI.

TRENCH WIDTH (SEE TRENCH WIDTH TABLE BELOW FOR MAXIMUM TRENCH -FINISHED GRADE - SEE TRENCH PAVEMENT DETAILS ON SHEET CU-7.1 -COMPACTED SUITABLE BACKFIL - APPROVED COMPACTED GRAVEL/CRUSHED STONE NO LEDGE CONDITION - MIDDLE BEDDING AREA (REFER TO NOTE 6) -BEDDING CONTROL LINE (BCL)


- 1. MAINTAIN UNIFORM TRENCH WIDTH TO 6" OVER PIPE.
- 2. IF SHEETING IS REQUIRED TO REMAIN, CUT OFF TWO (2) FEET BELOW FINISH
- 3. IF GROUNDWATER IS ENCOUNTERED, WRAP STONE WITH MIRAFI 140N FILTER FABRIC OR APPROVED EQUAL.
- 4. SEE PAVEMENT REPAIR DETAILS FOR ROAD WORK AREAS.
- 5. PROVIDE 6" MIN. BEDDING FOR AREAS OF EXCAVATION IN ROCK.
- 6. LOOSELY PLACE SUITABLE BACKFILL OR CLEAN WASHED $\frac{3}{4}$ " CRUSHED STONE IN MIDDLE BEDDING AREA. DO NOT COMPACT MIDDLE BEDDING AREA.
- 7. ALL TRENCHES SHALL BE SUFFICIENTLY WIDE TO ACCOMMODATE TRENCH BOX.
- 8. PER RIDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, APPROVED SUBGRADE SHOULD NOT CONSIST OF UNSUITABLE SOIL. UNSUITABLE SOILS IS DEFINED AS THOSE SOILS, OTHER THAN MUCK, WHICH DUE TO THEIR CONSOLIDATION PROPERTIES, DEGREE OF SATURATION, GRADATION, OR OTHER DELETERIOUS CHARACTERISTICS WILL NOT PROVIDE A STABLE SUPBRADE OR SIDE SLOPES, CANNOT BE USED AS, OR SUPPORT EMBANKMENT, OR CANNOT BE PLACED AND COMPACTED AS BACKFILL.

TREN	CH WIDTHS
PIPE SIZE	MAX (ONE PIPE)(a)
15" OR LESS	4'-0"
18"	5'-0"
24"	5'-6"
30"	6'-0"
36"	6'-6"
42"	7'-0"
48"	7'-6"
MANHOLES	O.D. + 6'-0"
CATCH BASINS'	O.D. + 6'-0"

a. FOR ROCK EXCAVATION SUBTRACT 1'-0"



TYPICAL PIPE TRENCH



DRAWN CHECK No DATE REVISIONS/DESCRIPTION BY 02/18/22 PROGRESS SET

Civil - Survey Structural Environmental Design

3102 East Main Road, Portsmouth RI 02871

Tel. 401.683.6630 www.nei-cds.com

SUMMER STREET APARTMENTS

IN CARE OF: CHRISTINE M. WEST, AIA | PRINCIPAL

3/25/22 DPR

KITE ARCHITECTS | ONE CENTRAL STREET | PROVIDENCE RI 02907 KITEARCHITECTS.COM |

94 SUMMER ST, PROVIDENCE, RI 02903

SHEET TITLE

401.272.0240 X117

PROPERTY RECORD

PLAT: 24, LOT: 640 ZONE: C-2 AREA: 1.16 ACRES

N/F: CROSSROADS RI


REF. NEI # 0019.198

CW@KITEARCHITECTS.COM


DETAILS & NOTES


RAWINGS MUST BE PRINTED IN COLOR TO BE VALII THIS NOTE SHOULD BE BLUE. IF THIS NOTE IS NO BLUE, PLEASE REPRINT IN COLOR OR CONTACT N

WATER MAIN AND STORM OR SANITARY SEPERATION TYPICAL THRUST BLOCK DETAIL




PROVIDENCE WATER HYDRANT DETAILS






TEMPORARY TRENCH PAVEMENT SECTION SCALE: N.T.S








NOTES: 1. REMOVE BYPASS CONNECTION AND AND RESTORE AREA ONCE WATER MAIN INSTALLATION HAS BEEN COMPLETED.

TEMPORARY BYPASS CONNECTION DETAIL

2. RESTRAIN ALL JOINTS.

SCALE: N.T.S



TYPICAL UTILITY SEPARATION


Civil - Survey Structural Environmental Design 3102 East Main Road, Portsmouth RI 02871 Tel. 401.683.6630 www.nei-cds.com

SHEET TITLE DETAILS & NOTES

SUMMER STREET APARTMENTS

IN CARE OF: CHRISTINE M. WEST, AIA | PRINCIPAL KITE ARCHITECTS | ONE CENTRAL STREET | PROVIDENCE RI 02907 KITEARCHITECTS.COM | 401.272.0240 X117 CW@KITEARCHITECTS.COM

PROPERTY RECORD 94 SUMMER ST, PROVIDENCE, RI 02903 PLAT: 24, LOT: 640 ZONE: C-2 AREA: 1.16 ACRES N/F: CROSSROADS RI REF. NEI # 0019.198




PROJECT #		DATE	DRAWN CHE		ECK	
21.0103		12/17/21	LD NKH			
No	DATE	REVISIONS/DESCRIPTION			BY	
1 02/18/22		PROGRESS SET			СВ	


DRAWINGS MUST BE PRINTED IN COLOR TO BE VALID THIS NOTE SHOULD BE BLUE. IF THIS NOTE IS NO BLUE, PLEASE REPRINT IN COLOR OR CONTACT NE

SCALE


C2.3





TRENCH GRASS RESTORATION SECTION





CONN. OF PR. WATER MAIN TO EX. WATER MAIN



















SHEET TITLE
DETAILS & NOTES

SUMMER STREET APARTMENTS

IN CARE OF: CHRISTINE M. WEST, AIA | PRINCIPAL KITE ARCHITECTS | ONE CENTRAL STREET | PROVIDENCE RI 02907 KITEARCHITECTS.COM | 401.272.0240 X117 CW@KITEARCHITECTS.COM

PROPERTY RECORD

94 SUMMER ST, PROVIDENCE, RI 02903


PLAT: 24, LOT: 640

ZONE: C-2

AREA: 1.16 ACRES

N/F: CROSSROADS RI

REF. NEI # 0019.198



lnei-de d

PROJECT #		DATE DRAWN C		CHE	CK
21.0103		12/17/21	LD	NKH	
No	DATE	REVISIONS/DESCRIPTION BY			BY
1	02/18/22	PROGRESS S	SET		СВ

DRAWINGS MUST BE PRINTED IN COLOR TO BE VALID THIS NOTE SHOULD BE BLUE. IF THIS NOTE IS NO BLUE, PLEASE REPRINT IN COLOR OR CONTACT NE


SCALE 1"=20'


C2.4

Parameter	Specification	Size	Notes
Sand	clean AASHTO M-6 or ASTM C-33 concrete sand	0.02" to 0.04"	Sand substitutions such as Diabase and Graystone #10 are not acceptable. No calcium carbonated or dolomitic sand substitutions are acceptable. No rock dust can be used for sand.
Underdrain gravel	RIDOT Specs. Sec. 300 AASHTO M-43	0.25" to 0.75"	Must be washed, clean gravel; refer to Appendix Section F.4.1, Part 2 for applicable material specs.
Geotextile Fabric (if required)	ASTM D-751 (puncture strength - 125 lb.) ASTM D-1117 (Mullen Burst Strength - 400 psi) ASTM D-1682 (Tensile Strength - 300 lb.)	0.08" thick equivalent opening size of #80 sieve	Must maintain 125 gpm per sq. ft. flow rate. Note: a 4" pea gravel layer may be substituted for geotextiles meant to separate filter layers.
Underdrain Piping	RIDOT Specs. Sec. 703 ASTM D-1785 or AASHTO M-278	4-6" rigid schedule 40 PVC	3/8" perf. @ 6" on center, 4 holes per row; minimum of 3" of gravel over pipes.
Concrete (Cast- in-place)	See RIDOT Specs. Sec. 600 f'c = 3500 psi, normal weight, air-entrained; reinforcing bars to meet ASTM 615-60	n/a	on-site testing of poured-in-place concrete required: 28 day strength and slump test; all concrete design (cast-in-place or pre-cast) not using previously approved local or RI standards requires design drawings sealed and approved by a RI-licensed structural PE.
Concrete (pre- cast)	See RIDOT Specs. Sec. 600 per pre-cast manufacturer	n/a	SEE ABOVE NOTE
non-rebar steel	ASTM A-36	n/a	structural steel to be hot-dipped galvanized ASTM A123

SAND FILTER MATERIAL SPECIFICATIONS







CONCRETE MINIMUM STRENGTH - 000 PSI @ 28 DAYS

DESIGN METHOD

STEEL REINFORCEMENT - ASTM A-615, GRADE 60

DESIGN SPECIFICATION — AASHTO LOAD FACTOR

DESIGN LOADING - AASHTO HS20-44

EARTH COVER O'-O" MIN. O'-O" MAX.

SECTION JOINT - SEE JOINT DETAIL

DESIGN NOTES




SHEET TITLE DETAILS & NOTES

SUMMER STREET APARTMENTS

IN CARE OF: CHRISTINE M. WEST, AIA | PRINCIPAL KITE ARCHITECTS | ONE CENTRAL STREET | PROVIDENCE RI 02907 KITEARCHITECTS.COM | 401.272.0240 X117 CW@KITEARCHITECTS.COM

PROPERTY RECORD 94 SUMMER ST, PROVIDENCE, RI 02903 PLAT: 24, LOT: 640 ZONE: C-2 AREA: 1.16 ACRES N/F: CROSSROADS RI REF. NEI # 0019.198




	PROJECT # 21.0103		DATE	DRAWN	CHE	CK
			12/17/21	LD	NKH	
	No	DATE	REVISIONS	S/DESCRIPT	ION	BY
	1	02/18/22	PROGRESS S	SET		СВ

DRAWINGS MUST BE PRINTED IN COLOR TO BE VALI THIS NOTE SHOULD BE BLUE. IF THIS NOTE IS NO BLUE, PLEASE REPRINT IN COLOR OR CONTACT N


C2.5


(1) 6" ROUND OPENINGS 7	N DRAIN PIPE (1) 6" ROUND OPENINGS 7 4" Ø SDR 35 UNDERDRAIN DRAIN PIPE
18" SAND	(6) 8"Ø OPENINGS (6) 6"Ø DIA PVC PIPES GROUTED IN (2) 6"Ø OPENINGS 18" SAND 18" GRAVEL
SECTION A-A	SECTION B-B



SECTION C-C

SAND FILTER SECTIONAL VIEWS 3 SAND
C2.5 SCALE: NTS





STORMWATER REPORT


Proposed Development Project Summer Street Apartments 94 Summer Street Providence RI 02903

Assessors Plat 24, Lot 640 Issued 3-25-22



Prepared by E. Eric Cordis, P.E.

NEI Job Number: 21.0103



Prepared by:

CONTENTS

1. INTRODUCTION	
2. EXISTING CONDITIONS	3
3. ANALYSIS METHODOLOGIES	4
4. HYDROLOGIC ANALYSIS (PRE AND POST)	6
5. CONCLUSIONS.	6
APPENDIX A: Background Information APPENDIX A.1: Site Location Map APPENDIX A.2: NRCS Soils Map AND SOILS INFORMATION APPENDIX A.3: Flood Insurance Rate Maps (FIRM)	
APPENDIX B: Soil Logs APPENDIX B.1: Test Hole Location Plan APPENDIX B.2: Soil Logs (RMA Geotech Report)	
APPENDIX C: HydroCAD Analyses APPENDIX C.1: Pre-development HydroCAD Analysis APPENDIX C.2: Post-development HydroCAD Analysis APPENDIX C.3: Water Quality Storm HydroCAD Analysis APPENDIX C.4: Stage Storage Tables Ex and Prop. APPENDIX D: Water Quality Calculations APPENDIX E: Existing and Proposed Drainage Figures (See attached plan set for 24x36 sheets)	


1. INTRODUCTION

On behalf of Crossroads RI (Applicant), Narragansett Engineering, Inc. (NEI) has prepared this Stormwater Management Report in support of a proposed residential housing redevelopment to an existing site ("the Site" or "the Project") located at 94 Summer Street., Providence Rhode Island.

The subject site is comprised of the parcel, Plat 24, Lot 640 Located on the lot bounded by Summer, Conduit, and Stewart Street. The site is zoned C-2 (Gen Commercial with a TOD (Traffic Sensitive Overlay District).

This project is not a "Land use with higher potential pollutant loads (LUHPPL)" as defined in the RISDISM. The Site location is shown below and provided in Appendix A.1.

Location Map – 94 Summer St, Providence, RI 02903



The Project includes a number of stormwater best management practices (BMPs) to control stormwater quality and quantity for the development. BMPs proposed for the project include treatment of roof runoff, and most impervious areas on the interior courtyard with sand filters using forebay settling with treatment of the water quality volume (WQv) and treatment of the surge or peak flows with (4) surge tanks.

Due to urban fill issues, there is no concentrated infiltration proposed. Landscape areas are proposed for tree planting and landscaping, but these areas will not be treating adjacent stormwater areas with concentrated infiltration.

Treated stomwater will be sent the sanitary sewer system (NBC) with a direct connection at the request of the city of Providence Engineering Department. The final design point (proposed DP1) is the same location as existing, the sanitary system south of the site at the NBC sanitary sewer main (20" diameter).

Storage tanks are used to control peak flows and orifice release of flows to keep flows such as post flow rates are less than existing flow rates.

This Stormwater Management Report provides supporting evaluation, documentation, analysis, and calculations to confirm that all components of the stormwater management system have been designed to comply with the requirements set forth in the latest edition of the "Rhode Island Stormwater Design and Installation Manual (RISDISM)."

2. EXISTING CONDITIONS

The subject site contains an existing paved parking lot (94 Summer St), currently used for vehicle parking. The site has been extensively graded, and is currently in a disturbed state, though topographically it slopes generally from east to west. The property is served by Providence Water, NBC Sewer, as well as National Grid Electric. The site is not located in a flood hazard zone, it is located in any TD (transportation District) overlay district

Currently, site stormwater runoff flows to the:

- South/West to the street gutter line, and final disposition in the NBC sanitary sewer via several catch basins ringing the site. (DP1)
- There is an area to the south east with is directed onto the project site, flows across and exits in the south west corner of the site to the street line, and hence to the sanitary sewer.

• .

GROUNDWATER AND SOIL EVALUATION


Based on NRCS mapping (see Appendix A.2: NRCS Soils Map), soils within the development areas of the Site are:

Mu, Merrimac-urban land complex. Class A, was used for the analysis.

(2) test pits, and (4) soil borings were performed at the site. These evaluations show that design SHGW depth is between 14'-20' from original grade. Ledge was encountered in the deep boring at 101.5 feet below grade. No bedrock outcrops are located on the property.

FEMA

Based on Fema FIRMette, dated 2-2-22 the project site is not located in a flood zone. See Appendix A.3: Flood Insurance Rate Maps (FIRMette).



DESIGN POINTS

As determined by NEI, based on existing site condition and topography along with the proposed development program, One Design Point has been used for the stormwater analysis.

• DP-1, NBC Sanitary sewer Summer Street

ANALYSIS METHODOLOGIES

The stormwater design was designed to exceed the requirements of the City of Providence and RISDISM (unless noted otherwise due to site constraints) via the application of several sand filter BMPs and water storage tanks for peak control. The analytical approach was to reduce peak flows for all storms events, and maximize stormwater treatment. As such, proposed watersheds were analyzed by adjusting the surface cover where appropriate, and recomputing HydroCAD. In addition, the model calculated separate runoff for pervious and impervious areas within each sub catchment, adjusted-Q approach to preserve the impervious runoff for stormwater flow.

To establish the study limits and down-gradient Design Point (DP1), a rainfall-runoff model in HydroCAD (Version 10.00-11) using standard Curve Number (CN) methodologies, the Soil Conservation Service (SCS) TR-20 runoff method, the Natural Resources Conservation Service (NRCS) unit hydrograph and time of concentration

methodologies). The Analytical approach for this application was to determine a range of frequency related flood outflow hydrographs routed to, or potentially impacted by, the development areas (1.2 in., 1-yr, 3-month, 2-yr, 10-yr, 25 yr and 100-yr).

Erodible Surface Assumptions

The entire area of the lot is to be reduced to below erodible surface for the water quality calculations.

Waiver requirements

Due to the urban fill, no concentrated soil infiltration will be allowed, so the recharge target levels will not be able to be reached.

PRE-DEVELOPMENT ANALYSIS

Under pre-development conditions, the Site stormwater runoff travels to the above-described Design Points, where peak discharge rates were evaluated for the WQ-Event (0-Storm), 1-year, 3 month, 2-year, 10-year, 25 year and 100- year storm events. (See Appendix C.1: Pre-development HydroCAD Analysis and Appendix E: Existing Site Watershed Plan.

POST DEVELOPMENT ANALYSIS

Under post-development conditions, the Site stormwater runoff travels to the above-described Design Point, where peak discharge rates were evaluated for the WQ-Event (0-Storm), 1-year, 3-month, 2 year, 10-year, and 100- year storm events. (See Appendix C.2: Pre-development HydroCAD Analysis and Appendix E: Existing Site Watershed Plan.

The intent of the design was to reduce post peaks at DP1 to reduce stress on the sanitary sewer system.

The water quality volume is directed to the sand filter tanks for the entire WQ storm. Flows larger than this amount are directed via an overflow weir to the storage surge tanks. Sand filters (after processing), and offsite flows are directed to the site storage tanks to buffer the peak flows prior to discharge.

By utilizing a bypass on the sand filters/forebays, the forebays and will be greatly reduced so that sediment re-suspension in the forebay areas is eliminated. This will promote the long-term service life of the sand filters themselves.

4. HYDROLOGIC ANALYSIS

The hydrologic analysis was performed using HydroCAD software for a 24-hour, Type III rainfall event for Providence County (1-year: 2.7 inches, 10-year: 4.9 inches, 100-year: 8.7 inches) and three points of analysis, "Design Point".

Table 1 provides a summary of this analysis, which shows that post-development peak discharge rates will be less than pre-development peak discharge rates for all storms up to and including the 100-year event. Due to the limited infiltration capacity on the property and the lined filter systems, volume control was not a primary objective. By a slight reduction in impervious area, the difference in the pre and post volumes is statistically insignificant. The post design peak flows were reduced at all three design points for all storm events in the analysis.

Table 1: Hydrologic Analysis Summary (See additional details in Appendix C)

DESIGN POINT	DESIGN STORM	Peak Flow (cfs)		Total Volume (Acre Feet)	
		EXISTING	PROP	EXISTING	PROPOSED
DP1	WQv	1.68	0.49	0.126	0.104
	3 Month NBC	3.26	1.60	0.177	0.146
	1-YEAR	4.01	2.20	0.316	0.263
	2-Year	4.93	2.92	0.393	0.326
	10-Year	7.37	5.28	0.597	0.498
	25-Year	7.37	6.87	0.597	0.630
	100-Year	13.13	9.53	1.084	0.920

The HydroCad model analysis shows that the proposed conditions are an improvement over existing conditions for total Peak Flow Rate for each model storm event (WQv,3 Month,1,2,10,25,100 year).

a. CONCLUSIONS

This project has been designed in accordance with the latest edition of the *RISDISM*, Section 3.2 Minimum Stormwater Management Standards, as summarized below and provided in other submission documents.

MINIMUM STORMWATER MANAGEMENT STANDARDS

1. Minimum Standard 1: LID Site Planning and Design Strategies

"LID Site planning and design strategies must be used to the maximum extent practicable in order to reduce the generation of the water runoff volume for both new and redevelopment projects."

LID site planning and design strategies have been employed on this project to the maximum extent practicable.

2. <u>Minimum Standard 2: Groundwater Recharge</u>

"Stormwater must be recharged within the same sub watershed to maintain base flow at predevelopment recharge levels to the maximum extent practicable."

The required recharge volume is calculated using the formula Re = (1"/12)(F)(I), where:

Re = Groundwater Recharge Volume

F = Recharge Factor, based on HSG for the project (Site is A; therefore, F = 0.60) I =

Contributing impervious area (AC)

Therefore, Re = $(1^{"}/12)(0.6)(42,658 \text{ sq ft}) = 2,132-FT^3$ (Required)

0 cf of concentrated infiltration is provided due to the presence of urban fill. Landscape areas are allowed to infiltrate, and hence the infiltration at the site is improved over existing.

This standard is not meet due to urban fill presence at the site. Compliance with this standard is technically impractical.

3. Minimum Standard 3: Water Quality

"Stormwater runoff must be treated before discharge."

Pre-treatment: Pre-treatment equal to 25% of the water quality volume is required for parking lots, driveways, and sidewalks; no pre-treatment is required for stormwater generated from the building roofs entering infiltration ponds. For the parking lot, access drives, and sidewalks pre-treatment of is achieved using a sedimentation forebay prior to the sand filters (2P).

See appendix D for sand filter calculations. A forebay is used prior to each sand filter unit. Discharges are sent to storage tanks, which has a controlled discharge by the 8" outlet pipe in the final tank.

The forebays and the sand filter are designed as off line devices to reduce peak flow impacts due to larger storms. Bypasses begin to occur after about 1.2 inches of rainfall, which is the full wqs volume. The sand filters and bypass can hold or bypass a 100-year storm with no adverse effects.

The sand filters systems are sized to hold more than 75% of the WQv going to each filter (in a static condition).

Accordingly, the pre-treatment and treatment requirements of Minimum Standard 3 have been satisfied. Pretreatment practices are Forebays for sand filters.

4. Minimum Standard 4: Conveyance and Natural Channel Protection

"Protection for natural channels downstream must be supplied by providing 24-hour extended detention of the one-year, 24-hour Type III design storm event runoff volume."

HydroCAD calculations are provided in Appendix C; these calculations show that the resulting flow rates (total of all design points) is less in a post construction configuration in comparison to the existing peak flow rates.

Minimal Infiltration measures are possible at the site due to shallow groundwater levels.

The sand filter system is designed to release the CPv volume. The system meets the volume and rate requirements to meet the CPv standard.

5. Minimum Standard 5: Overbank Flood Protection

"Downstream overbank flood protection must be provided by attenuating the post-development peak discharge rate to the pre-development levels for the 10-year and 100-year, 24-hour Type III design storm events. In addition, designers must demonstrate that runoff from the Site for storms up to the 100-year, 24-hour Type III design storm events actually reach proposed structural practices designed to meet this criterion."

The stormwater management system has been designed to attenuate the post-development peak discharge rates to pre-development levels for the 1-, 10 and 100-year storm events. Additionally, a hydraulic analysis of the system provides confirmation that the stormwater management system has been adequately sized to convey the 100-year storm to the proposed structural practices via the proposed stormwater collection system or by overland flow in an extreme event.

Therefore, Minimum Standard 5 has been satisfied. A Stormwater management Plan checklist or "Appendix A (RISDISM)" has been prepared and is provided under separate cover. This document provides data to show compliance with this standard.

6. <u>Minimum Standard 6:</u> Redevelopment and Infill Projects

"The purpose of this minimum standard is to establish the alternative requirements for projects or portions of a project where existing impervious areas will be redeveloped or where the Site qualifies as infill."

This project is considered a redevelopment or infill project; therefore Minimum Standard 6 is applicable to this project. Calculations are provided in Appendix D.

7. Minimum Standard 7: Pollution Prevention

"All development Sites require the use of source control and pollution prevention measures to minimize the impact that the land use may have on stormwater runoff quality."

Pollution prevention is addressed in the Soil Erosion and Sedimentation Control Plan provided under separate cover, which confirms that Minimum Standard 7 has been satisfied.

8. Minimum Standard 8: Land Uses with Higher Potential Pollutant Loads

"Stormwater discharges from land uses with higher potential pollutant loads (LUHPPLs) require the use of specific source control and pollution prevention measures and the specific stormwater BMPs approved for such use."

In accordance with the *RISDISM* definition, the project is not considered a "land use with higher potential pollutant loads;" therefore Minimum Standard 8 is not applicable to this project.

9. Minimum Standard 9: Illicit Discharges

"All illicit discharges to stormwater management systems are prohibited."

There are no existing or proposed illicit discharges to the stormwater management system; therefore Minimum Standard 9 is not applicable to this project.

10. Minimum Standard 10: Construction Erosion and Sedimentation Control

"Erosion and sedimentation control (ESC) practices must be utilized during the construction phase as well as during any land disturbing activities. ESC practices must meet the following minimum design criteria: temporary sediment trapping practices must be sized to store 1 inch of runoff from the contributing area or per the sediment volume method (Rhode Island Soil Erosion and Sediment Control Handbook), whichever is greater; and temporary conveyance practices must be sized to handle the peak flow from the 10-year, 24-hour Type III design storm."

NEI developed Site plans that include a Proposed Site Plan, Sedimentation and erosion control and demo plan, Utility construction Plans, and Detail sheets. These plans have been developed in conformance with the checklist provided in RIPDES CGP Section 5. These plans illustrate the minimum construction erosion and sedimentation controls necessary to meet the requirements of Minimum Standard 10 at the start of construction. Details to control erosion and sediment transport throughout construction are also provided on this plan set.

11. Minimum Standard 11: Stormwater Management Operation and Maintenance

"The stormwater management system, including all structural stormwater controls and conveyances, must have an operation and maintenance plan to ensure that it continues to function as designed."

An Operations and Maintenance Plan has been developed and will be provided to the reviewer(s) under separate cover prior to final approval by the Providence engineering department. This document demonstrates compliance with Minimum Standard 11.

APPENDIX A:

Background Information